

I12 Series Features:

- 12,000 lbs. capacity for raising most passenger cars, trucks and vans.
- The I12 is third party certified by ALI.
- Hydraulic cylinders in each column
 - Full stroke
 - Cylinder rod concealed inside carriage
- Overhead cable equalization.
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions (4-1/2" and 8-1/2") are standard.
- Spring operated arm restraints, disengage at floor level.
- Padded overhead height limit switch bar.
- Durable powder coat finish - standard color of lift is blue with yellow arms. Red lift with yellow arms also available at no extra cost.



Shown: Model I12
12,000 lbs. capacity

Available Options:

- Adapter storage bracket kit
- Special truck adapters
- Air/Electric work station with air regulator and oiler



Shown: Model I12
12,000 lbs. capacity

Specifications	I12
Capacity	12,000 lbs. (5443kg)
Rise Height	82-1/2" (2095mm) with adapters
Adjustable Overall Height	165-1/4" (4197mm), 177" High Setup (4496mm)
Overall Width	150-3/8" (3822mm)
Drive Through	109-1/2" (2781mm)
Floor to Overhead Switch	159-3/8" Low (4051mm), 169-1/2" High (4305)
Front Arm Reach	Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm)
Rear Arm Reach	Min. 38-1/2" (978mm), Max. 57-1/2" (1461mm)
Lifting Pad Height	6" (152mm)
Lifting Pad Height w/Short Ext.	10-1/2" (267mm)
Lifting Pad Height w/High Ext.	14-1/2" (368mm)
Width Between Columns	123-1/4" (3131mm)
Motor	2 HP
Voltage	208v - 230v
Speed of Rise	60 seconds

Specifications subject to change without notice or liability



Forward Lift
996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329
www.forwardlift.com

Li# Forward I12_2009.10

©2009 Forward Lift, Forward Lift is a brand of R.L. Consolidated, A Dover Company. All rights reserved. Unless otherwise indicated, Forward Lift, R.L. Consolidated, Dover and all other trademarks are property of Dover Corporation and its affiliates.